

KASTO, Inc.

**3002 Venture Court
Export, PA 15632**

Sales: Phone 724-325-5600 – Fax 724-325-5611

Parts/Service: Phone 724-325-5605 – Fax 724-325-5612

E-Mail: sales@kastoinc.com



KASTO UNIBLOC STACKING CRADLE SYSTEM



TECHNICAL DATA

CRADLE SIZE [Inside Dimensions w x h (inches)]	LOAD CAPACITY Per Cradle	<u>STACKING LIMIT</u>
30.3 x 9.5	6,600 lbs.	14
30.3 x 11.8	6,600 lbs.	12
30.3 x 15.7	6,600 lbs.	10
30.3 x 23.6	6,600 lbs.	7
30.3 x 31.5	6,600 lbs.	5
42.1 x 9.5	6,600 lbs.	14
42.1 x 11.8	6,600 lbs.	12
42.1 x 15.7	6,600 lbs.	10
42.1 x 23.6	6,600 lbs.	7
42.1 x 31.5	6,600 lbs.	5

The necessary spreader beam(s) are designed to carry two or three layers simultaneously. For optimum performance, dual hoist cranes (swing-free if possible) are needed with the proper load-carrying capacity.

Depending on the product's length, 2 cradles (for 20-24' lengths) or 3 cradles (for 40' + lengths) per bundle are required.

**PLEASE CONTACT OUR SALES DEPARTMENT AT 724-325-5600
FOR MORE DETAILED INFORMATION OR A CUSTOMIZED QUOTE ON THIS SYSTEM!**