

KASTO, Inc.

**3002 Venture Court
Export, PA 15632**

Sales: Phone 724-325-5600 – Fax 724-325-5611

Parts/Service: Phone 724-325-5605 – Fax 724-325-5612

E-Mail: sales@kastoinc.com



Technical Data Sheet. KASTOdisc M 7

Cutting range:

Cutting range	90° round	full material	2.76 in.	70 mm
Cutting range	90° round	tubes	3.94 in.	100 mm
Cutting range	90° square	tubes	3.54 x 3.54 in.	90 x 90 mm
Cutting range	90° flat	square	5.31 x 3.15 in.	135 x 80 mm
Cutting range	+/- 45° round	full material	2.76 in.	70 mm
Cutting range	+/- 45° round	tubes	3.94 in.	100 mm
Cutting range	+/- 45° square	tubes	3.54 x 3.54 in.	90 x 90 mm
Cutting range	+/- 45° flat	square	3.94 x 3.15 in.	100 x 80 mm
Cutting range	+ 60° round	full material	2.76 in.	70 mm

KASTO, Inc.

3002 Venture Court
Export, PA 15632

Sales: Phone 724-325-5600 – Fax 724-325-5611

Parts/Service: Phone 724-325-5605 – Fax 724-325-5612

E-Mail: sales@kastoinc.com



Cutting range	+ 60° round	tubes	3.15 in.	80 mm
Cutting range	+ 60° square	tubes	2.76 x 2.76 in.	70 x 70 mm
Cutting range	+ 60° flat	square	2.76 x 3.15 in.	70 x 80 mm

Dimensions and Weight:

Length	17.72 in.	450 mm
Width	31.50 in.	800 mm
Height	66.93 in.	1700 mm
Material support height	35.43 in.	900 mm
Total weight	594 lbs.	270 kg

Power characteristics:

Power	1.72 / 2.38 HP	1/31/9 IW
Voltage	220/440 Volt/60 Hz	400 Volt / 50 Hz
Cutting speed	108.24/216.48 ft./min or 55.76/111.52 ft./min	33/66 m/min or 17/34 m/min
Dimensions of saw blade	12.40 x 0.10 x 1.26 in.	315 x 2.5 x 32 mm

Electrical equipment:

Supply voltage 220/440 Volts, 60 Hz, 3 phase
Control voltage 24 V DC
Other voltages upon request at additional cost.

Safety requirements:

The machine is offered with reference to the valid safety requirements according to DIN EN ISO 12100-1, DIN EN ISO 12100-2

Color:

Light grey RAL 7035, Structural painting

**PLEASE CONTACT OUR SALES DEPARTMENT AT 724-325-5600
FOR MORE DETAILED INFORMATION OR A QUOTE ON THIS MACHINE!**